

## Introduction

ZM300 is a multi-biometric, fully automatic smart lock with a built-in indoor monitoring screen. This smart lock can unlock through facial recognition, smartphone fingerprint, IC card and pin code password. Also, ZM300 will lock the door, when users open the door with a smartphone. ZM300 is compatible with ZSmart, an application designed for home automation.

#### **Features**



## 3D Structured Light Facial Recognition

3D Structured Light Facial Recognition Quick verification and unlock



## Supports Remote Mobile App

Unlock and manage the lock from anywhere



#### **Audio Instructions**

User-friendly audio prompts, support English and Spanish



## Capacitive Fingerprint Sensor

Fast verification for dry and rough fingers



## **Smart Alerts**

Receive real-time notifications of low battery, hijack and offline



## **Lock Automatically**

The deadbolt will protrude when you close the door immediately, no extra action required



## **Temporary Access**

Share digital keys valid for specific time to friends or guests



#### Wi-Fi Communication

Ensure a fast and stable by Wi-Fi IEEE 802.11b



### Random Passcode

Add random digits to protect your passcode from prying eyes



#### **Emergency Charging Port**

Charging via the micro-USB port



## Built-in Doorbell

Built-in electronic doorbell Need not deploy a physical doorbell



#### Capture Photos / Videos

Capture photos/videos and save in TF card (support max. 128 GB), who requests remote unlock or press the doorbell

## **Mobile Application**















App Control



Check Records

Lock Setup

# **Specifications**

-	
Material	Aluminum Alloy and Tempered Glass
Capacity	Face: 50; IC S50 Card: 50; Fingerprint: 100; Password: 100
Events Log	Access events records by ZSmart APP Doorbell calling history; Wrong Password Alert; Remote unlocking history (Free cloud storage for 6 months)
Face Recognition Technology	3D Structured Light Facial Recognition
Facial Recognition Speed	<1s
Facial Recognition Distance	0.5m to 1m
Supported Application	ZSmart App
Display LCD Screen	3.5 inch
Power Supply	4,200mA; lithium battery
Emergency Interface	Micro USB 5V
Mortise Type	Chinese standard mortise (6068)
MCBF	>100,000
Communication	Wi-Fi
Operating Temperature	-25°C to 75°C
Operating Humidity	20% RH to 90% RH
Random Password	Supports
Doorbell	Supports
Audio Prompts	English
Application Scenarios	Duplexes, townhouses, apartments, condos, and residential buildings
Door Thickness (mm)	45 to 60 (customizable)
Dimensions (L*W*H)	Outdoor unit: 393.5*74.5*21mm Indoor unit: 393.5*74.5*25.6mm

